

NIRVANA

TO THE HAPPINESS INSIDE

With Pimapen Nirvana, the superior window of energy efficiency, your living spaces will breathe and the chaos of the world will stay outside your home thanks to the unique heat, sound, dust, air and water insulation.





Profile Width	80 mm
Number of Cubicles	6
Profile Class	Class A/ Class B (TS EN 12608-1)
Gasket System	Triple Gasket System: Internal-External and Central Gaskets.
Gasket Type - Color	TPE - Gray / Black
Glazing Thicknesses (mm)	24, 30, 36, 44, 52
Uf	0,95 W/m ² K

PROFILE

The main profiles of the Pimapen Nirvana Premium Window and Door Systems are 80 mm in width. The 6-cubicle profiles and non-staining elastic gaskets of gray and black these systems employ provide not only heat and sound insulation, but also air, water and dust insulation. The triple gasket system consisting of internal-external and central gaskets contributes to the heat and sound insulation and, protects the equipment used in the casement openings from corrosion making them long lasting.

GLAZING COMBINATIONS

There are glazing beads allowing for the use of double glazing, triple glazing and panels in the width of 24-30-36-44-52 mm. The profiles feature a lower heat transmission value ($U_f=0.95 \text{ W/m}^2\text{K}$). They allow for the use of triple glazing units of 44 mm ($U_g=0,6-0,7 \text{ W/m}^2\text{K}$). The heat transmission value of the windows from the Pimapen Nirvana series applied with this type of glazing is $^*U_w = 0.78 \text{ W/m}^2\text{K}$ delivering a superior level of heat insulation. (* : as calculated).

DESIGN

The casement profile of the Pimapen Nirvana Premium Window and Door System is of a self-drip design delivering an elegant look. The glazing area gets wider due to the optimized PVC door profile height delivering a spacious space without compromising on the view. The special designed glazing beads offer an elegant way to join the PVC profiles with the glazing. A visual integrity is offered on the interior surface and, the joinery and wall joints with a self-sill frame PVC profile.

EQUIPMENT

Deliver a higher level of security in the secure glazing combinations up to 52 mm. Possible to apply window and door systems with enhanced security thanks to alternative equipment. Different opening types allow for a functional usage.